


# TPS950

## Face Recognition Terminal



OS	Android 8.1 Linux (Optional)
Processor	Octa-Core 1.8GHz or above
Memory	2GB DDR, 16GB eMMC 3GB DDR, 32GB eMMC (Optional)
Display	5.5-inch, 720*1280
Keypad	1 Reset Key
Camera	Single-lens Camera (RGB), 2MP Dual-lens Camera (RGB+IR), 2MP+1.3MP (Optional) 3D Depth Sensing Camera (Optional)
LED light	White LED
Contactless Card Reader (Optional)	ISO14443 Type A/B, Mifare, ISO18092 compliant
Communications	Ethernet/WiFi/Bluetooth LTE (Optional)
Peripheral Ports	1 DC Input, 1 Micro USB, 1 RJ45, 1 Door Lock, 1 Wiegand, 1 RS485
Audio	Digital Audio Speaker, Microphone
Power Supply	12V/2A
Bracket (Optional)	Wall Mount Bracket, Turnstile Mount Bracket
Dimensions (mm)	188 (L)*94 (W)*27 (H)
Environmental	Operating temperature: -5°C ~ 45°C (Optional: -20°C ~ 50°C) Storage temperature: -25°C ~ 60°C
MDM (Optional)	Mobile Device Management
Certification	CE



Note: Reserve the right to change the parameters without prior notice.